

			KF(Rd)-50LW
Power supply			220V/50Hz
Performance			
Capacity	Cooling	Btu/h	17000
		W	5000
	Heating	Btu/h	19000(+3400)
		W	55000(+1000)
Noise	Indoor	dB(A)	<48
	Outdoor	dB(A)	<56
Air circulation		m ³ /h	900
Suitable area		m ²	22~34
Power			
Input power	Cooling	W	1920
	Heating	W	1920(+1000)
Rated Current	Cooling	A	8.8
	Heating	A	8.8(+4.5)
Dimension			
Indoor unit	Net	mm	485x260x1687
	Shipping	mm	565x375x1777
Outdoor unit	Net	mm	930x330x600
	Shipping	mm	995x390x650
Weight			
Indoor unit	Net/shipping	Kg	38 / 43
Outdoor unit	Net/shipping	Kg	51 / 55

1. The test of those above are stipulated on country's standard pipe's average length: 5m, if over please fill up additional refrigerant.

Cooling: Indoor Circulating Temp: 27°C DB; 19°C WB Outdoor Temp: 35°C DB; 24°C WB

Heating: Indoor Circulating Temp: 20°C DB; Outdoor Temp: 7°C DB; 6°C DB

			KF(Rd)-70LW	KF(Rd)-120LW
Power supply			220V/50Hz	220V/50Hz
Performance				
Capacity	Cooling	Btu/h	24000	41000
		W	7000	12000
	Heating	Btu/h	26000(+5000)	44000(+8500)
		W	7700(+1500)	13000(+2500)
Noise	Indoor	dB(A)	<52	<54
	Outdoor	dB(A)	<60	<64
Air circulation		m ³ /h	1200	1700
Suitable area		m ²	30~50	60~90
Power				
Input power	Cooling	W	2600	4700
	Heating	W	2600(+1500)	4700(+2500)
Rated Current	Cooling	A	12.3	8.2
	Heating	A	12.3(+6.8)	8.2(+11.8)
Dimension				
Indoor unit	Net	mm	1795x565x320	1795x565x400
	Shipping	mm	1855x625x375	1855x625x455
Outdoor unit	Net	mm	930x330x730	985x355x1030
	Shipping	mm	1025x395x790	1105x435x1120
Weight				
Indoor unit	Net/shipping	Kg	45 / 50	53 / 58
Outdoor unit	Net/shipping	Kg	61 / 66	95 / 100

1. The test of those above are stipulated on country's standard pipe's average length: 5m, if over please fill up additional refrigerant.

Cooling: Indoor Circulating Temp: 27°C DB; 19°C WB Outdoor Temp: 35°C DB; 24°C WB

Heating: Indoor Circulating Temp: 20°C DB; Outdoor Temp: 7°C DB; 6°C DB

			KF(Rd)-140LW
Power supply			380V/50Hz
Performance			
Capacity	Cooling	Btu/h	48000
		W	14000
	Heating	Btu/h	52000(+8500)
		W	15000(+2500)
Noise	Indoor	dB(A)	<55
	Outdoor	dB(A)	<65
Air circulation		m ³ /h	1700
Suitable area		m ²	70~100
Power			
Input power	Cooling	W	5200
	Heating	W	5200(+2500)
Rated Current	Cooling	A	8.9
	Heating	A	8.9(+11.8)
Dimension			
Indoor unit	Net	mm	1915x370x577
	Shipping	mm	1990x465x652
Outdoor unit	Net	mm	460x360x1300
	Shipping	mm	1080x440x1390
Weight			
Indoor unit	Net/shipping	Kg	53 / 58
Outdoor unit	Net/shipping	Kg	122 / 127

1. The test of those above are stipulated on country's standard pipe's average length: 5m, if over please fill up additional refrigerant.
Cooling: Indoor Circulating Temp: 27°C DB; 19°C WB Outdoor Temp: 35°C DB; 24°C WB
Heating: Indoor Circulating Temp: 20°C DB; Outdoor Temp: 7°C DB; 6°C DB