

220-240V-, 50Hz 380-415V-, 50Hz

Item			KFR-26GW/C	KFR-34GW/C	KFR-50GW	KFR-70GW
Capacity	Cooling	Btu/h	9000	12000	18000	24000
		W-frig/h	2600	3400	5000	7000
	Heating	Btu/h	9000	12600	18000	24000
		W-frig/h	2600	3500	5000	7000
Power supply		V-Hz	220/50	220/50	220/50	220/50
Working range		V	220V,+15%-10%	220V,+15%-10%	220V,+15%-10%	220V,+15%-10%
air circulation		m ³ /h	400	500	750	900
Rated input	Cooling	W	930	1300	1900	2500
	Heating	W	930	1300	1900	2500
Rated current	Cooling	A	4.6	6.2	8.9	11.8
	Heating	A	4.6	6.2	8.9	11.8
Weight	Indoor	Kg	11.2/14.8	11.2/14.8	14.5/18.5	16.5/19
	Outdoor	Kg	32/37	35/45	51/56	61/66
Dimension	Indoor	mm	760x260x195	815x275x183	1015x320x188	1080x330x213
	Outdoor	mm	822x315x250	830x320x540	912x346x616	930x370x730
Package size	Indoor	mm	605x242x520	875x335x255	1115x375x255	1155x385x290
	Outdoor	mm	685x342x585	905x360x600	995x390x650	1025x395x865
Noise	Indoor	dB (Lo)	24	28	36	40
	Outdoor	dB	48	50	56	58
Pipe dimension	Liquid	inch	1/4	1/4	1/4	3/8
	Gas	inch	3/8	1/2	1/2	5/8
EER	Cooling	W/W	2.7	2.7	2.6	2.8
	Heating	W/W	2.7	2.6	2.6	2.8
Refrigerant charged		g	650	760	1300	2150