

			FP-5.0KMQ	FP-6.3KMQ	FP-8.0KMQ
Power supply			220V/50Hz	220V/50Hz	220V/50Hz
Performance					
Capacity	Cooling	Btu/h	8500	12000	17000
		W	2500	3500	5000
	Heating	Btu/h	10000	14000	22000
		W	3000	4200	6500
Noise		dB(A)	<42	<42	<45
Air circulation		m ³ /h	500/420/340	630/560/480	800/720/630
Control method			Remote or Wall Pad	Remote or Wall Pad	Remote or Wall Pad
Power					
Input power		W	45	50	65
Motor current		A	0.19	0.23	0.32
Technical information					
Water flow		m ³ /h	0.52	0.62	0.86
Water pressure drop		KPa	14	16	18
Cond. pipe size		mm	26	26	26
Water connection	In	Inch	G3/4	G3/4	G3/4
	Out	Inch	G3/4	G3/4	G3/4
Connection method			Socket	Socket	Socket
Main body					
Net dimension		mm	570x570x256	570x270x256	570x270x256
Net weight		Kg	18.5	25	25
Panel					
Net dimension		mm	650x650x30	650x650x30	650x650x30
Net weight		Kg	2.2	2.2	2.2

1. Outlet air static pressure is 0Pa.

2. 27°C DB / 19.5°C WB entering air temperature, 7°C entering water and 12°C leaving water temperature.

3. 20°C DB entering air temperature, 60°C entering water and 50°C leaving water temperature.